



BGBF10 - Lincat Blu Blast Chiller - 10 Trays

Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly

- ✔ Quickly and efficiently pull down the temperature of cooked foods
- ✔ Perfect for large batch cooking, where large quantities of food need to be brought down to storage temperature quickly
- ✔ Reduce a product's core temperature from 90°C to 3°C within 90 minutes
- ✔ With shock freezing cycle - allows the nutritional properties, appearance and flavour of a product to be maintained after thawing
- ✔ Core probe needle as standard
- ✔ Indirect air flow guarantees a perfect temperature throughout the unit
- ✔ GN1/1 and Euronorm 600 x 400 compatible - load 10 trays onto the side racks
- ✔ Side racks removable without tools for easy cleaning
- ✔ Easy-to-use digital controls - simple buttons for soft blast chilling, hard blast chilling, and shock freezing cycles, as well as manual time/temperature controls
- ✔ Auto-defrost function
- ✔ Radiused interior corners enable easy cleaning
- ✔ Reversible self-closing door with 105 degree stop
- ✔ High efficiency 60mm cyclopentane insulation - zero ODP (Ozone Depletion Potential) and only a low GWP (Global Warming Potential), providing excellent thermal efficiency
- ✔ Wide magnetic gasket gives effective seal, easily removable for cleaning
- ✔ Hygienic and robust design - Grade 304 stainless steel interior and exterior, radiused interior corners to promote easy cleaning

Specifications

Summary

Brand	Lincat
Range	Blu
Power Type	Electric
Unit Type	Free-standing
Available in UK Only	No
UK Warranty	2 Years Parts and Labour (3 Years on Compressor)
Export Warranty	Contact your local dealer
GTIN	5056105123378

Power and Performance

Total Power kW	2.8
Temperature Range °C	+20 to -40
Temperature Control	Electronic
Cooling Capacity Watts	4,906W / 1,072W
Climate Class	5

Key Specifications

Lockable Door	No
Number of Doors	1
Reversible Door	Yes
Number of Shelf Positions	10
Refrigerant Type	R452a
Construction/Finish	304 Grade S/S Ext/Int
Base Mounting	Castors
Insulation Material/Thickness	Cyclopentane / 60 mm
Maximum Ambient Temperature °C	38
Auto Defrost	Yes
HACCP Compliant	Yes
Number of Shelves	0
Shelf Supports	Anti-tilt
Integral Handle	Yes
Self Close Door	Yes

Capacity

Gastronorm Capacity	GN1/1, Euronorm
Chilling Capacity kg	30
Chilling Time mins	90
Freezing Capacity kg	20
Freezing Time mins	270

Weights and Dimensions		Supply Connections	
------------------------	--	--------------------	--

Unit Height (External) mm	1630	Requires Installation	Yes
Unit Width (External) mm	800	Requires Electrical Supply	Yes
Unit Depth (External) mm	830	UK 3 Pin Plug	No
Net Weight Kg	195	Requires Hardwiring	Yes
		Electrical Supply Rating Watts	2,800
		Single Phase Amps	11
		Single Phase Voltage	230

Shipping	
----------	--

Packed Weight Kg	200
Packed Height cm	176
Packed Width cm	85
Packed Depth cm	88



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm